

LIGHTWEIGHT CONDUCTOR COVERS

Lightweight Conductor Covers are ideal to cover long spans when weight is a consideration. They can be applied when wearing rubber gloves or with a fiberglass stick. Available with an eye for application with shotgun sticks. These covers have a voltage rating of 26.4 kV*. The inside diameter is 2". This product can connect with Salisbury 1.5" I.D. Class 3 or 4 flexible cover-up equipment.

The **21826 Lightweight Conductor Cover** is a six (6', 1.8m) foot, cover rated Class 4 (36.6 kV*). It is applied using rubber gloves when following appropriate company work rules. The inside diameter is 3" making it useful on a wide range of conductor sizes.

The unique "connector-stop" molded into one end prevents covers from overlapping during installation. This eliminates wasted time when trucks have to be moved to reconnect sections that did not couple correctly. This cover is also compatible with Salisbury 1.5" I.D. Class 3 or 4 flexible rubber line hose.

All of our lightweight covers are made from safety orange Type I high density cross link polyethylene.

*guarded Ø to guarded Ø.



21315



21172



21173



21234 Adapter Eye



21826



Conductor Covers connect easily with either plastic or rubber line hose



21826 Unique Connector Stop

Cat. No.	Description ft. (m)	ASTM Voltage Class	Grade	Weight ea. lbs. (kgs)
27 kV CONDUCTOR COVERS				
21172	5' (1.5) Cover w/ Eye	3	2	4.0 (1.8)
21173	5' (1.5) Cover w/o Eye	3	--	3.0 (1.4)
21315	5' (1.5) Cover w/ 4' (1.2) Fiberglass Stick	3	1	5.0 (2.25)
21234	Adapter Eye	3	--	1.5 (0.7)
35kV CONDUCTOR COVER				
21826	6' (1.8) Cover	4	--	6.5 (2.95)

All guards are tested to ASTM F712 and are manufactured to ASTM F968 specifications